

WANECO®WB462

Textured Paint

Product Description

WANECO®WB462 Textured Paint is a new-generation crack-resistant, waterproof textured exterior coating manufactured using advanced flexible acrylic emulsion and textured inorganic materials through modern processing techniques. Its unique reinforced formulation delivers superior crack resistance, enhanced waterproofing, and breathability, while providing versatile shapes and diverse textures for natural decorative effects.

Product Characteristics

Offers artistic decorative effects with diverse textured finishes. Exceptional flexibility effectively resists wall cracking. Features outstanding waterproofing, breathability, adhesion, and weather resistance.

Recommended Applications

Can be applied to surfaces such as cement mortar, plaster, cement asbestos board, concrete, or putty. Suitable for interior and exterior wall decoration in residential buildings, villas, hotels, office buildings, and other structures.

Technical Specifications

Physical Parameters

Color	Natural color or customer-specified color
Gloss	Matte
Solids By Weight	Approx. 70% (may vary depending on specific colors and designs)
Theoretical Spreading Rate	1.5-.3.5 m ² /kg (may vary depending on desired application effect)

Surface Preparation

The surface to be coated must be thoroughly dry, clean, and free of oil and other contaminants. It must also be smooth, solid, and free of defects. The wall moisture content must be <8%, and the pH must be <10.

Application Guidance

Application Method

Embossed Effect	Apply using spray guns or rollers. Coverage is approximately 2-3kg/m ² .
Finishing Effect	Apply using a trowel. Coverage is approximately 2-3kg/m ² .
Scratch Effect	Apply using a trowel or scraper. Usage is approximately 1.5-3.5kg/m ² .

Construction Tools

Scrapers, rollers, spray guns, etc.

Thinner

Clean Water

Cleaning Agent: Clean Water

Drying Time

Surface Temperature	20°C
Surface Dry	4 hours
Drying time varies with changes in temperature and humidity.	

Ambient Temperature

5°C~40°C. Avoid application when relative humidity exceeds 85%.

Mixing and Thinning

After opening the WANECO®WB462 can, thoroughly stir the paint inside. If necessary, add an appropriate amount of water according to the instructions. Do not over-dilute. Do not add other paints, organic solvents, or powders.

Ventilation

For the safety of construction personnel and the proper performance of this product, all areas of the construction site must be well ventilated.

Packaging and Storage

Packaging

Single-component, packaging specifications vary by color configuration.

Storage

Product storage must comply with national regulations. Store in a cool, well-ventilated area at a temperature not below 0°C, avoiding heat and ignition. Containers must be kept tightly closed.

Shelf life

1 year

Warning

May cause eye and skin irritation. Vapors may cause respiratory irritation in sensitive individuals. May cause skin sensitization. Avoid breathing vapors. Avoid contact with eyes and skin. Use eye, ear, and skin protection, and wear an appropriate respirator to avoid potential respiratory irritation. After use, thoroughly wash skin with water. If discomfort occurs, consult a physician. Wash clothing before reuse. If breathing has stopped, perform artificial respiration, preferably mouth-to-mouth, and seek medical attention. Burns: Exothermic reactions may cause product to become excessively hot. Handle mixtures with caution. Wear gloves. First Aid: If product contacts eyes, immediately flush with water for at least 15 minutes. Remove contaminated clothing and shoes. Wash exposed skin with soap.

Before and during use, observe all safety labels on the packaging. Consult the Safety Data Sheet and comply with relevant national or local government safety regulations.

Statement

The information listed in this document is reliable. Each value provided is calculated as theoretical data based on the product formulation. Upon request, our company can disclose the internal standard measurement methods used to determine any of the above data. Since usage conditions are beyond the manufacturer's control, this information is provided without warranty. The product is intended for professional use only. For any inquiries, please contact our company.

Our Technical Support and Customer Service Center is available to provide consultation and application technical services regarding the product. We welcome your inquiries via mail or phone. National Customer Service Hotline: 400-059-1116 ext. 3.